

7/pats

10/551800

JC20 Rec'd PCT/PTO 30 SEP 2005

Description

PORTABLE WIRELESS APPARATUS

5

Technical Field

The present invention relates to a portable wireless apparatus such as a mobile phone or a PHS.

Background Art

10

The portable wireless apparatus such as the mobile phone has advanced the size reduction of a terminal. The portable wireless apparatus having an antenna packaged in its casing has been increasing in number.

15

Fig. 7A presents a perspective view of an openable portable wireless apparatus of the prior art, and Fig. 7B presents a sectional view of the portable wireless apparatus of Fig. 7A.

20

In Fig. 7A and Fig. 7B, first casing 121 having main display 105 on its surface is covered with front case 103 of first casing 121 and back case 104 of first casing 121 and is equipped therein with first circuit board 101. Moreover, second casing 122 input unit 108 on its surface is covered with front case 106 of second casing 122 and back case 107 of second casing 122 and is equipped therein with second circuit board 102. Circuit board connector 110 is housed in hinge 109 for connecting the two casings in a foldable manner, and connects first circuit board 101 and

25

second circuit board 102.

In the case of the openable portable wireless apparatus, as shown in Fig. 7A and Fig. 7B, an antenna 111 is frequently configured in the vicinity of hinge 119 or in the end portion of the casing.

This portable wireless apparatus of the prior art is disclosed in JP-A-2003-8320, for example.

In case, however, antenna 111 is configured in hinge 109 of the portable wireless apparatus of the prior art thus far described, it comes closer to the human body in speeches. Therefore, the portable wireless apparatus is troubled by a problem that its communication performances are degraded as the telephone by the electric power absorption of the human body.

Disclosure of the Invention

A portable wireless apparatus comprises: a first casing including a front case on the side having a main display, a back case on the opposite side of the front case, and a first circuit board; a second casing including a front case on the side having an input unit, a back case on the opposite side of the front case, and a second circuit board; a circuit board connector for electrically connecting the first circuit board and the second circuit board; a hinge having the circuit board connector for connecting the first casing and the second casing

in a foldable manner; an antenna connected to the hinge side of the second circuit board; a first parasitic element configured in the front case and made longer than the electrical length of the antenna; and a second parasitic element configured in the back case and made shorter than the electrical length of the antenna.

Brief Description of the Drawings

Fig. 1A is a perspective view of a portable wireless apparatus according to one embodiment of the invention.

Fig. 1B is a sectional view of the portable wireless apparatus of Fig. 1A.

Fig. 2A is a radiation pattern of the portable wireless apparatus according to the embodiment of the invention.

Fig. 2B is a radiation pattern of the portable wireless apparatus of the prior art.

Fig. 3 is a sectional view of a portable wireless apparatus according to the embodiment of the invention.

Fig. 4A is a perspective view of a portable wireless apparatus according to one embodiment of the invention.

Fig. 4B is a sectional view of the portable wireless apparatus of Fig. 4A.

Fig. 5A is a perspective view of a portable wireless apparatus according to one embodiment of the invention.

Fig. 5B is a sectional view of the portable wireless

apparatus of Fig. 5A.

Fig. 6A is a perspective view of a portable wireless apparatus according to one embodiment of the invention.

Fig. 6B is a sectional view of the portable wireless
5 apparatus of Fig. 6A.

Fig. 7A is a perspective view of the portable wireless apparatus of the prior art.

Fig. 7B is a sectional view of the portable wireless apparatus of the prior art.

10

Description of Reference Numerals and Signs

1	First circuit board
2	Second circuit board
3	Front case of first casing
15 4	Back case of first casing
5	Main display
6	Front case of second casing
7	Back case of second casing
8	Input unit
20 9	Hinge
10	Circuit board connector
11	Antenna
12	First parasitic element
13	Second parasitic element
25 14	Third parasitic element

- 15 Fourth parasitic element
- 16 First connector
- 17 Second connector
- 18 First short-circuiting portion
- 5 19 Second short-circuiting portion
- 21 First casing
- 22 Second casing

Detailed Description of the Preferred Embodiments

10 The invention contemplates to solve the problems of the portable wireless apparatus of the prior art thus far described, and has an object to provide a portable wireless apparatus having a configuration for reducing the degradation in communication performances in speeches.

15 (Embodiment 1)

 The invention will be described on Embodiment 1 with reference to the accompanying drawings.

 Fig. 1A is a perspective view showing a portable wireless apparatus according to Embodiment 1 of the invention, and Fig.
20 1B is a sectional view of the portable wireless apparatus according to Embodiment 1 of the invention.

 In Fig. 1A and Fig. 1B, first casing 21 having main display
5 on its surface is equipped with front case 3 and back case 4 and therein with first circuit board 1. Second casing 22
25 having input unit 8 on its surface is equipped with surface

case 6 and back case 7 and therein with second circuit board 2. Circuit board connector 10 is housed in hinge 9 for connecting first case 21 and second case 22 in an openable manner. First circuit board 1 and second circuit board 2 are connected by circuit board connector 10. Antenna 11 is connected with second circuit board 2 on the side of hinge 9. Main display 5 displays the letters, images and so on of communications, operations and accessory functions at portable wireless apparatus 30. First circuit board 1 and second circuit board 2 act to execute the communications, operations and accessory functions at portable wireless apparatus 30. Input unit 8 is used by the user so as to input the letters, symbols or instructions, when the user executes the communications, operations and accessory functions at portable wireless apparatus 30.

In front case 3 of first casing 21, there is configured first parasitic element 12, which has a longer electrical length than the frequency of antenna 11 and acts as a reflector. In back case 4 of first casing 21, on the other hand, there is configured second parasitic element 13 which has a shorter electrical length than the frequency of antenna 11 and which has the action as a director. First parasitic element 12 and second parasitic element 13 are packaged and configured in the end portions of the casing at positions pairing each other. The electrical length implies the effective length at the time when first parasitic element 12 and second parasitic element

13 act as antennas. With this configuration, a directive control for decreasing the radiation toward the human body in the speeches but directing the same in the opposite direction can be made to reduce the degradation of the communication characteristics in the speeches. Portable wireless apparatus 30 in Embodiment 1 of the invention is thus configured.

In Fig. 1A and Fig. 1B, first parasitic element 12 and second parasitic element 13 are disposed longitudinally of Fig. 1A. In the invention, it is needless to say that first parasitic element 12 and second parasitic element 13 may also be disposed transversely of Fig. 1A.

With reference to Fig. 2A and Fig. 2B, here is described the comparison of the radiation patterns of the cases, in which the configuration of this embodiment is used and not. Fig. 2A shows radiation patterns of the case, in which the configuration of the embodiment is used, and Fig. 2B shows radiation patterns of the case, the configuration of the embodiment is not used, that is, the radiation patterns in the configuration of the prior art.

Fig. 2A shows the radiation patterns in the sectional directions of first casing 21 and second casing 22 of portable wireless apparatus 30. Fig. 2B shows the radiation patterns in the sectional directions of first casing 121 and second casing 122 of the portable wireless apparatus. In the ordinary using state of portable wireless apparatus 30, the upward direction

of the faces of the two Figures are directed vertically upward,
and the leftward direction of the faces of the two Figures is
oriented toward the human body side whereas the rightward
direction of the faces of the two Figures is oriented backward
5 of the human body. In Fig. 2A, radiation pattern 24 is that
of portable wireless apparatus 30 of this embodiment on the
human body side, and radiation pattern 23 is that of portable
wireless apparatus 30 of this embodiment on the opposite side
of the human body. Radiation pattern 23 is larger than radiation
10 pattern 24. In case portable wireless apparatus 30 of this
embodiment is used, a stronger radiation occurs on the opposite
side of the human body, and the radiation to occur on the body
side is weaker. In Fig. 2B, on the other hand, radiation pattern
26 is that of portable wireless apparatus of the prior art on
15 the human body side, and radiation pattern 25 is that of portable
wireless apparatus of the prior art on the opposite side of
the human body. Radiation pattern 25 and radiation pattern
26 are substantially identical. In other words, the radiation
to occur on the human body side is not weak, in case the portable
20 wireless apparatus of the prior art is used.

In this embodiment, first parasitic element 12 acts as
the reflector so that it can suppress the radiation toward the
human body, and second parasitic element 13 acts as the director
so that it can establish the radiation directivity backward
25 of the human body. As shown by radiation pattern 24 and radiation

pattern 25 in Fig. 2A, therefore, it is possible to confirm that the radiation gain backward of the human body is high whereas the radiation gain toward the human body is low. The directivity can be more turned backward of the human body especially by
5 setting first parasitic element 12 to a length larger than the half wavelength of a predetermined frequency band and second parasitic element 13 to a length smaller than the half wavelength of the predetermined frequency band. The predetermined frequency is used for the transmissions/receptions in portable
10 wireless apparatus 30. Here, first parasitic element 12 and second parasitic element 13 are conductors having wavelengths generally shorter than those in an ideal space. This shortening extent is generally called the "shortening percentage". Therefore, it goes without saying that the wavelength or the
15 unit for defining the aforementioned length of first parasitic element 12 or second parasitic element 13 contains the case, in which the shortening percentage is considered.

Moreover, the user grips second casing 22, but first parasitic element 12 and second parasitic element 13 are
20 configured on the side of first casing 21 so that the characteristic influences on the parasitic elements can be reduced even with the gripping.

Moreover, first parasitic element 12 and second parasitic element 13 are so individually configured on the end portion
25 of first casing 21 as to oppose each other. As a result, the

influences from the remaining parts of the portable wireless apparatus can be reduced to give more directivity to the opposite side of the human body.

With this configuration of the invention, in the communicating state near the human body, it is possible to reduce such a degradation of the communication performances of the portable wireless apparatus as might otherwise be caused by the power absorption of the human body because the antenna unit approaches the human body.

Here, the means for realizing first parasitic element 12 and second parasitic element 13 is exemplified by plating front case 3 or back case 4 or by fixing a metal sheet on the same. Thus, it is possible to produce the portable wireless apparatus inexpensively.

By thus using first parasitic element 12 acting as the reflector and second parasitic element 13 acting as the director, it is possible to provide the portable wireless apparatus, which can have the radiation directivity backward of the human body so that it can reduce the degradation of the communication performances in the speech.

The section of a portable wireless apparatus of another configuration of this embodiment is shown Fig. 3. In this configuration, portable wireless apparatus 30 is equipped with first short-circuiting portion 18 for connecting parasitic element 12 and first circuit board 1 and second short-circuiting

portion 19 for connecting second parasitic element 13 and first circuit board 1.

By thus connecting first parasitic element 12 with first circuit board 1 through first short-circuiting portion 18, as in this configuration, first parasitic element 12 can be made longer than one quarter wavelength so that it can be shortened by the monopole action of the GND of the board to about one half as short as that of the case, in which short-circuiting portion 18 is not used. Likewise, by connecting second parasitic element 13 with first circuit board 1 through second short-circuiting portion 19, second parasitic element 13 can be made shorter than one quarter wavelength so that it can be shortened to about one half as short as that of the case, in which short-circuiting portion 19 is not used.

In the description thus far made, first parasitic element 12 is configured in front case 3 of first casing 21, and second parasitic element 13 is configured in back case 4 of first casing 21. However, the invention can achieve an effect to control the directivity although influenced by the gripping, even if first parasitic element 12 is arranged in front case 6 of second casing 22 and if second parasitic element 13 is arranged in back case 7 of second casing 22.

In the description thus far made, moreover, first casing 21 is configured of front case 3 and back case 4, and second casing 22 is configured of front case 6 and back case 7. In

the invention, however, either of the front and back sides of each casing may be formed of a case whereas the other may be formed of a cover.

(Embodiment 2)

5 The invention will be described on Embodiment 2 with reference to the accompanying drawings.

Fig. 4A is a perspective view showing a portable wireless apparatus according to Embodiment 2 of the invention, and Fig. 4B is a sectional view of the portable wireless apparatus
10 according to Embodiment 2. Here, the description on the components having configurations similar to those of Embodiment 1 is omitted by designating them by the common reference numerals.

The difference between Embodiment 2 and foregoing
15 Embodiment 1 resides in that at least one of first parasitic element 12 and second parasitic element 13 is configured generally into a shape of letter substantially "U" along the casing shape.

This configuration makes it possible to enlarge the
20 lengths of first parasitic element 12 and second parasitic element 13 while suppressing the influences of first circuit board 1 and second circuit board 2 and the parts packaged in those boards. Therefore, the configuration can match such a low frequency as needs a large element length.

25 In Fig. 4A and Fig. 4B, first parasitic element 12 and

second parasitic element 13 are configured on the side of first casing 21. However, the effect to control the directivity although influenced by the gripping can be obtained, even if first parasitic element 12 and second parasitic element 13 are
5 configured on the side of second casing 22.

In Embodiment 2, moreover, the side failing to form the C-shape may be located at any one.

(Embodiment 3)

The invention will be described on Embodiment 3 with
10 reference to the accompanying drawings.

Fig. 5A is a perspective view showing a portable wireless apparatus according to Embodiment 3 of the invention, and Fig. 5B is a sectional view of the portable wireless apparatus according to Embodiment 3 of the invention. Here, the
15 description on the components having configurations similar to those of Embodiment 1 is omitted by designating them by the common reference numerals.

In Fig. 5A and Fig. 5B: front case 3 of first casing 21 is equipped with first parasitic element 12; back case 4 of
20 first casing 21 with second parasitic element 13; front case 6 of second casing 22 with third parasitic element 14; and back case 7 of second casing 22 with fourth parasitic element 15. First parasitic element 12 and third parasitic element 14 are connected with each other through first connector 16. Moreover,
25 second parasitic element 13 and fourth parasitic element 15

are connected with each other through second connector 17. First connector 16 and second connector 17 are formed of a flexible conductor.

5 This configuration makes it possible to connect the conductor element on the side of first casing 21 and the conductor element on the side of second casing 22 through the flexible connector. As a result, the element lengths of the parasitic elements can be enlarged while configuring the openable portable wireless apparatus so that the portable wireless apparatus can
10 match the low frequency needing the large element length.

Here, first parasitic element 12 to fourth parasitic element 15, and first connector 16 and second connector 17 are individually set to have such lengths as can act as the reflector or the director, as has been described in connection with
15 Embodiment 1.

In Fig. 5A and Fig. 5B, on the other hand, first parasitic element 12 to fourth parasitic element 15 are formed straight. However, first parasitic element 12 to fourth parasitic element 15 may also be formed generally into a shape of letter
20 substantially "U" along the shapes of first casing 21 and second casing 22.

(Embodiment 4)

The invention will be described on Embodiment 4 with reference to the accompanying drawings. Here, the description
25 on the components having configurations similar to those of

Embodiment 1 is omitted by designating them by the common reference numerals.

Fig. 6A is a perspective view showing a portable wireless apparatus according to Embodiment 4 of the invention, and Fig.

5 6B is a sectional view of the portable wireless apparatus according to Embodiment 4.

In Fig. 6A and Fig. 6B: front case 3 of first casing 21 is equipped with first parasitic element 12 matching a first predetermined frequency band; back case 4 of first casing 21
10 with second parasitic element 13 matching the first predetermined frequency band; front case 6 of second casing 22 with third parasitic element 14 matching a second predetermined frequency band; and back case 7 of second casing 22 with fourth parasitic element 15 matching the second
15 predetermined frequency band.

Here, first parasitic element 12 to fourth parasitic element 15 are set to such individual lengths as can act as the reflector or the director, as has been described in connection with Embodiment 1.

20 This configuration makes it possible to reduce the performance degradation in the speeches near the human body for a plurality of frequency bands, i.e., the first frequency band and the second frequency band.

Although the description thus far made has been directed
25 to the case of the two frequency bands, the invention can also

apply that configuration, too, to three or more frequency bands.

In Fig. 6A and Fig. 6B, on the other hand, first parasitic element 12 to fourth parasitic element 15 are formed straight, but may also be formed generally into a shape of letter substantially "U" along the shapes of first casing 21 and second casing 22. In Fig. 6A and Fig. 6B, moreover, third parasitic element 14 and fourth parasitic element 15 are configured on the side of second casing 22, but may be disposed on the side of first casing 21. Then, it is possible to further reduce the gripping influences.

In Fig. 6A and 6B, moreover, first parasitic element 12, second parasitic element 13, third parasitic element 14 and fifth parasitic element 15 are disposed longitudinally of Fig. 6A. In the invention, it is needless to say that first parasitic element 12, second parasitic element 13, third parasitic element 14 and fourth parasitic element 15 may also be disposed transversely of Fig. 6A.

As has been described in connection with the embodiments thus far described, the portable wireless apparatus of the invention are made at least such that the first parasitic element longer than the electrical length of the antenna is configured in the front case, and such that the second parasitic element shorter than the electrical length of the antenna is configured in the back case. By controlling the radiation directivity with those first parasitic element and second parasitic element,

the directivity can be given in the opposite direction backward of the human body in the speeches thereby to provide the portable wireless apparatus, which can reduce the characteristic degradation in the speeches.

5

Industrial Applicability

The invention can provide a portable wireless apparatus capable of reducing the characteristic degradation in the speeches close to the human body so that it is used near the

10 human body.